

Remove spigot with horseshoe shape tool from underside of tank **if dishwashing.**





Hold reset button for 10 seconds until it blinks **green.**



Soak filter for 15 minutes, then **rinse** for 10 seconds.



Fill reservoir with cool tap water and enjoy!



Install filter then **twist** and **lock** to align.



© 2023 All rights reserved. Distributed by Kaz USA, Inc., a Helen of Troy Company, 400 Donald Lynch Blvd, Marlborough, MA 01752. PUR* is a trademark of Helen of Troy Limited.

For detailed instructions / Para instrucciones en español: PUR.com/Support

PUR

Filter Light flashes **green** with every pour.



Replace filter when light flashes **red**.



Reset after every **filter change**.





Filter will last up to **2 months**.

This PUR Dispenser is not intended to purify water. **Do Not** use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. PUR does not filter microbes.



PUR Replacement Filters



PUR PLUS CRF-950Z (Included with system.)



PUR PPF900Z™ (Certified with system, sold separately.)

Filter Capacity: 40 gallons (151 liters), up to 2 months Max Water Temp: 82°F (28°C) Min Water Temp: 34°F (2°C)

Independently Certified



System Tested and Certified by WQA against NSF/ANSI Standards 42, 53 and 401 for the reduction of the claims specified on the Performance Data Sheet.



System Tested and Certified by NSF International against NSF/ANSI Standards 42, 53 and 401 for the reduction of the claims specified on the Performance Data Sheet.



Effective water filter that does not remove fluoride from water

Visit **PUR.com/PDS** for performance data sheet and filter replacement information.

NSF/ANSI Standard 401 has been deemed as "incidental contaminants/emerging compounds." Incidental contaminants are those compounds that have been detected in drinking water supplies at trace levels. While occurring at only trace levels, these compounds can affect the public acceptance/perception of drinking water quality.